






8150
brache per sollevamento 1t viola nastro piatto a due strati, asole rinforzate, poliestere alta tenacità (PES)

CE

UNI EN 1492-1



art.	art.	L m		
081500005	8150 0,5-T1	0,5	30	1
081500010	8150 1-T1	1	30	1
081500015	8150 1,5-T1	1,5	30	1
081500020	8150 2-T1	2	30	1
081500025	8150 2,5-T1	2,5	30	1
081500030	8150 3-T1	3	30	1
081500035	8150 3,5-T1	3,5	30	1
081500040	8150 4-T1	4	30	1
081500050	8150 5-T1	5	30	1
081500060	8150 6-T1	6	30	1
081500080	8150 8-T1	8	30	1

				$\beta=0^{\circ}+45^{\circ}$	$\beta=45^{\circ}+60^{\circ}$
30					
30	1t	0,8t	2t	1,4t	1t
60	2t	1,6t	4t	2,8t	2t
90	3t	2,4t	6t	4,2t	3t
120	4t	3,2t	8t	5,6t	4t
150	5t	4,0t	10t	7,0t	5t
180	6t	4,8t	12t	8,4t	6t
240	8t	6,4t	16t	11,2t	8t
300	10t	8,0t	20t	14,0t	10t